NSN 6145-00-194-3636

Electrical Wire - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-00-194-3636

Cross Sectional Shape: Round Tempurature Rating: 80.0 degrees celsius Tracer Color: Green first tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification:
80.0 degrees celsius Tracer Color: Green first tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
Tracer Color: Green first tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
Green first tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
28 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
Material: Plastic polyvinyl chloride 1st position primary insulation single conductor
Plastic polyvinyl chloride 1st position primary insulation single conductor
Material Specification:
Qq-w-343, soft federal specification single material response core conductor single conductor
Surface Treatment:
Tin core conductor single conductor
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A077a0
Mil-std (military Standard):
Mil-i-3930 spec.