NSN 6145-00-254-7199

Electrical Wire - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-00-254-7199

Cross Sectional Shape: Round Tempurature Rating: 90.0 degrees celsius Tracer Color: Orange second tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor Shelf Life:
90.0 degrees celsius Tracer Color: Orange second tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
90.0 degrees celsius Tracer Color: Orange second tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Tracer Color: Orange second tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor
Surface Treatment: Tin core conductor single conductor
Tin core conductor single conductor
•
Shalf Life:
Offen Life.
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A077a0
Mil-std (military Standard):
Mil-i-3930 spec.