## NSN 6145-00-284-0629

Electrical Wire - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-00-284-0629

Round Tempurature Rating: 80.0 degrees celsius Cross Section Outside Diameter: 0.067 inches Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-+3930 spec.	Cross Sectional Shape:
Tempurature Rating: 80.0 degrees celsius Cross Section Outside Diameter: 0.067 inches Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor Shelf Life: N/a Unit of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	•
80.0 degrees celsius  Cross Section Outside Diameter: 0.067 inches  Strand Quantity Per Conductor: 7 single conductor  Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor  White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A07730 Mil-std (military Standard):	
Cross Section Outside Diameter:  0.067 inches  Strand Quantity Per Conductor:  7 single conductor  Conductor Form:  Stranded single conductor  Round Conductor Size:  22 awg single conductor  Strand Awg Size Per Conductor:  30 single conductor  Voltage Rating:  1000.0 root mean square (rms) operating voltage single conductor  Color:  White 1st position cover single conductor  Material:  Plastic polyvinyl chloride 1st position primary insulation single conductor  Material Specification:  Qq-w-343, soft federal specification single material response core conductor single conductor  Surface Treatment:  Tin core conductor single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A077a0  Mil-std (military Standard):	
Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	
Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg: A077a0 Mil-std (military Standard):	
7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg: A077a0 Mil-std (military Standard):	
Conductor Form: Stranded single conductor Round Conductor Size: 22 awg single conductor Strand Awg Size Per Conductor: 30 single conductor Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor Color: White 1st position cover single conductor Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	
Stranded single conductor  Round Conductor Size: 22 awg single conductor  Strand Awg Size Per Conductor: 30 single conductor  Voltage Rating: 1000.0 root mean square (rms) operating voltage single conductor  Color: White 1st position cover single conductor  Material: Plastic polyvinyl chloride 1st position primary insulation single conductor  Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor  Surface Treatment: Tin core conductor single conductor  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig: A077a0  Mil-std (military Standard):	7 single conductor
Round Conductor Size:  22 awg single conductor  Strand Awg Size Per Conductor:  30 single conductor  Voltage Rating:  1000.0 root mean square (rms) operating voltage single conductor  Color:  White 1st position cover single conductor  Material:  Plastic polyvinyl chloride 1st position primary insulation single conductor  Material Specification:  Qq-w-343, soft federal specification single material response core conductor single conductor  Surface Treatment:  Tin core conductor single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A077a0  Mil-std (military Standard):	Conductor Form:
22 awg single conductor  Strand Awg Size Per Conductor:  30 single conductor  Voltage Rating:  1000.0 root mean square (rms) operating voltage single conductor  Color:  White 1st position cover single conductor  Material:  Plastic polyvinyl chloride 1st position primary insulation single conductor  Material Specification:  Qq-w-343, soft federal specification single material response core conductor single conductor  Surface Treatment:  Tin core conductor single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig: A077a0  Mil-std (military Standard):	Stranded single conductor
Strand Awg Size Per Conductor:  30 single conductor  Voltage Rating:  1000.0 root mean square (rms) operating voltage single conductor  Color:  White 1st position cover single conductor  Material:  Plastic polyvinyl chloride 1st position primary insulation single conductor  Material Specification:  Qq-w-343, soft federal specification single material response core conductor single conductor  Surface Treatment:  Tin core conductor single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A077a0  Mil-std (military Standard):	Round Conductor Size:
30 single conductor  Voltage Rating:  1000.0 root mean square (rms) operating voltage single conductor  Color:  White 1st position cover single conductor  Material:  Plastic polyvinyl chloride 1st position primary insulation single conductor  Material Specification:  Qq-w-343, soft federal specification single material response core conductor single conductor  Surface Treatment:  Tin core conductor single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig: A077a0  Mil-std (military Standard):	22 awg single conductor
Voltage Rating:  1000.0 root mean square (rms) operating voltage single conductor  Color:  White 1st position cover single conductor  Material:  Plastic polyvinyl chloride 1st position primary insulation single conductor  Material Specification:  Qq-w-343, soft federal specification single material response core conductor single conductor  Surface Treatment:  Tin core conductor single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A077a0  Mil-std (military Standard):	Strand Awg Size Per Conductor:
1000.0 root mean square (rms) operating voltage single conductor  Color: White 1st position cover single conductor  Material: Plastic polyvinyl chloride 1st position primary insulation single conductor  Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor  Surface Treatment: Tin core conductor single conductor  Shelf Life: N/a Unit Of Measure: Demilitarization: No  Fiig: A077a0 Mil-std (military Standard):	30 single conductor
Color: White 1st position cover single conductor  Material: Plastic polyvinyl chloride 1st position primary insulation single conductor  Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Voltage Rating:
White 1st position cover single conductor  Material:  Plastic polyvinyl chloride 1st position primary insulation single conductor  Material Specification:  Qq-w-343, soft federal specification single material response core conductor single conductor  Surface Treatment:  Tin core conductor single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A077a0  Mil-std (military Standard):	1000.0 root mean square (rms) operating voltage single conductor
Material: Plastic polyvinyl chloride 1st position primary insulation single conductor Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Color:
Plastic polyvinyl chloride 1st position primary insulation single conductor  Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor  Surface Treatment: Tin core conductor single conductor  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	White 1st position cover single conductor
Material Specification: Qq-w-343, soft federal specification single material response core conductor single conductor Surface Treatment: Tin core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Material:
Qq-w-343, soft federal specification single material response core conductor single conductor  Surface Treatment: Tin core conductor single conductor  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Plastic polyvinyl chloride 1st position primary insulation single conductor
Surface Treatment:  Tin core conductor single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A077a0  Mil-std (military Standard):	Material Specification:
Tin core conductor single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:  A077a0  Mil-std (military Standard):	Qq-w-343, soft federal specification single material response core conductor single conductor
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Surface Treatment:
N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Tin core conductor single conductor
Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Shelf Life:
Demilitarization:  No Fiig: A077a0 Mil-std (military Standard):	N/a
No Fiig: A077a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A077a0 Mil-std (military Standard):	<del></del>
Fiig: A077a0 Mil-std (military Standard):	Demilitarization:
A077a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A077a0
Mil-i-3930 spec.	Mil-std (military Standard):
	Mil-i-3930 spec.