## NSN 6145-00-630-0385

Electrical Power Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-00-630-0385

Tempurature Rating: 105.0 degrees celsius Cross-sectional Height: 0.095 inches Cross-sectional Width: 0.190 inches Conductor Quantity: 2 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 18 awg all conductors Strand Awg Size Per Conductor: 30 all conductors Conductor Arrangement And Quantity: 2 twisted together w/no outer covering Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Cuface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life:
105.0 degrees celsius  Cross-sectional Height: 0.095 inches  Cross-sectional Width: 0.190 inches  Conductor Quantity: 2  Strand Quantity Per Conductor: 19 all conductors  Conductor Form: Stranded all conductors  Round Conductor Size: 18 awg all conductors  Strand Awg Size Per Conductor: 30 all conductors  Conductor Arrangement And Quantity: 2 twisted together w/no outer covering  Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment: Tin core conductor all conductors  Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
Cross-sectional Height:  0.095 inches  Cross-sectional Width:  0.190 inches  Conductor Quantity:  2  Strand Quantity Per Conductor:  19 all conductors  Conductor Form:  Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:  2 twisted together w/no outer covering  Voltage Rating:  600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment:  Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
Cross-sectional Width: 0.190 inches Conductor Quantity: 2 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 18 awg all conductors Strand Awg Size Per Conductor: 30 all conductors Conductor Arrangement And Quantity: 2 twisted together w/no outer covering Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Cuface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
Cross-sectional Width: 0.190 inches Conductor Quantity: 2 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 18 awg all conductors Strand Awg Size Per Conductor: 30 all conductors Conductor Arrangement And Quantity: 2 twisted together w/no outer covering Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Color: White core conductor first conductor Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
O.190 inches  Conductor Quantity: 2  Strand Quantity Per Conductor: 19 all conductors  Conductor Form: Stranded all conductors  Round Conductor Size: 18 awg all conductors  Strand Awg Size Per Conductor: 30 all conductors  Conductor Arrangement And Quantity: 2 twisted together w/no outer covering  Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment: Tin core conductor all conductors  Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
Conductor Quantity:  2  Strand Quantity Per Conductor:  19 all conductors  Conductor Form:  Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:  2 twisted together w/no outer covering  Voltage Rating:  600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment:  Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
Strand Quantity Per Conductor:  19 all conductors  Conductor Form: Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:  2 twisted together w/no outer covering  Voltage Rating:  600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment:  Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
Strand Quantity Per Conductor:  19 all conductors  Conductor Form: Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:  2 twisted together w/no outer covering  Voltage Rating:  600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment:  Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
Conductor Form: Stranded all conductors Round Conductor Size: 18 awg all conductors Strand Awg Size Per Conductor: 30 all conductors Conductor Arrangement And Quantity: 2 twisted together w/no outer covering Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Color: White core conductor first conductor Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
Conductor Form: Stranded all conductors Round Conductor Size:  18 awg all conductors Strand Awg Size Per Conductor: 30 all conductors  Conductor Arrangement And Quantity: 2 twisted together w/no outer covering  Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors  Color: White core conductor first conductor  Surface Treatment: Tin core conductor all conductors  Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:  2 twisted together w/no outer covering  Voltage Rating:  600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment:  Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:  2 twisted together w/no outer covering  Voltage Rating:  600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment:  Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
18 awg all conductors  Strand Awg Size Per Conductor: 30 all conductors  Conductor Arrangement And Quantity: 2 twisted together w/no outer covering  Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment: Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:  2 twisted together w/no outer covering  Voltage Rating:  600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment:  Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
30 all conductors  Conductor Arrangement And Quantity: 2 twisted together w/no outer covering  Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors  Color: White core conductor first conductor  Surface Treatment: Tin core conductor all conductors  Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
Conductor Arrangement And Quantity:  2 twisted together w/no outer covering  Voltage Rating:  600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment:  Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
2 twisted together w/no outer covering  Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors  Color: White core conductor first conductor  Surface Treatment: Tin core conductor all conductors  Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors  Color: White core conductor first conductor  Surface Treatment: Tin core conductor all conductors  Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
600.0 root mean square (rms) operating voltage all conductors  Color:  White core conductor first conductor  Surface Treatment:  Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
Color: White core conductor first conductor Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
White core conductor first conductor  Surface Treatment:  Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
Tin core conductor all conductors  Surface Treatment Specification:  Astm b33-63 assn standard single treatment response core conductor all conductors
Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors
Astm b33-63 assn standard single treatment response core conductor all conductors
•
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
<b>Demilitarization:</b> No
No
No Fiig: