NSN 6145-00-803-0663

Electrical Wire - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-00-803-0663

Cross Sectional Snape: Round Tempurature Rating: -55.0 degrees celsius and 115.0 degrees celsius Cross Section Outside Diameter: 0.063 inches Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Stranded single conductor Strand Wissingle conductor Voltage Rating: 0.00.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard): Mil-m-20693 spec.	
Tempurature Rating: -55.0 degrees celsius and 115.0 degrees celsius Cross Section Outside Diameter: 0.063 inches Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 25 single conductor Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: Na Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Cross Sectional Shape:
-55.0 degrees celsius and 115.0 degrees celsius Cross Section Outside Diameter: 0.063 inches Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm ba3-63 asan standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A077a0 Mil-std (military Standard):	
Cross Section Outside Diameter: 0.063 inches Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: Va Unit Of Measure: Demilitarization: No Fig: A077a0 Mil-std (military Standard):	
Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A077a0 Mil-std (military Standard):	
Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A07730 Mil-std (military Standard):	Cross Section Outside Diameter:
7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A07730 Mil-std (military Standard):	0.063 inches
Conductor Form: Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Strand Quantity Per Conductor:
Stranded single conductor Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	7 single conductor
Round Conductor Size: 20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plestic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A077a0 Mil-std (military Standard):	Conductor Form:
20 awg single conductor Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Stranded single conductor
Strand Awg Size Per Conductor: 28 single conductor Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg: A077a0 Mil-std (military Standard):	Round Conductor Size:
28 single conductor Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	20 awg single conductor
Voltage Rating: 600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Strand Awg Size Per Conductor:
600.0 root mean square (rms) operating voltage single conductor Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	28 single conductor
Color: Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Voltage Rating:
Red 1st position cover single conductor Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	600.0 root mean square (rms) operating voltage single conductor
Material: Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Color:
Plastic polyamide 2nd position jacket single conductor Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Red 1st position cover single conductor
Material Specification: Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Material:
Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Plastic polyamide 2nd position jacket single conductor
Surface Treatment: Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Material Specification:
Tin core conductor single conductor Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Mil-m-20693, type 3, grade e military specification single material response 2nd position jacket single conductor
Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Surface Treatment:
Astm b33-63 assn standard single treatment response core conductor single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Tin core conductor single conductor
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Surface Treatment Specification:
N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Astm b33-63 assn standard single treatment response core conductor single conductor
Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	N/a
No Fiig: A077a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A077a0 Mil-std (military Standard):	<u></u>
Fiig: A077a0 Mil-std (military Standard):	Demilitarization:
A077a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A077a0
	Mil-std (military Standard):