NSN 6145-00-809-3659

Electrical Wire - Page 1 of 1

Mil-m-2069-3 spec.



View Online at https://aerobasegroup.com/nsn/6145-00-809-3659

| Cross Sectional Shape: |
|--|
| Round |
| Tempurature Rating: |
| 105.0 degrees celsius |
| Cross Section Outside Diameter: |
| 0.163 inches |
| Strand Quantity Per Conductor: |
| 37 single conductor |
| Conductor Form: |
| Stranded single conductor |
| Round Conductor Size: |
| 12 awg single conductor |
| Strand Awg Size Per Conductor: |
| 28 single conductor |
| Voltage Rating: |
| 600.0 root mean square (rms) operating voltage single conductor |
| Color: |
| White 1st position cover single conductor |
| Material: |
| Plastic polyamide 4th position jacket single conductor |
| Material Specification: |
| Mil-y-1-140 military specification single material response 2nd position braid, non-metallic single conductor |
| Surface Treatment: |
| Tin core conductor single conductor |
| Surface Treatment Specification: |
| Astm b33-63 assn standard single treatment response core conductor single conductor |
| Test Data Document: |
| As50861/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 813435086/3-12-9 professional/industrial association specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A077a0 |
| Mil-std (military Standard): |