NSN 6145-00-964-1230

Electrical Special Purpose Cable - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6145-00-964-1230

| Cross Sectional Shape: |
|--|
| Round |
| Tempurature Rating: |
| -65.0 degrees celsius and 200.0 degrees celsius |
| Cross Section Outside Diameter: |
| 0.086 inches |
| Conductor Quantity: |
| 2 |
| Strand Quantity Per Conductor: |
| 26 all conductors |
| Conductor Form: |
| Stranded all conductors |
| Round Conductor Size: |
| 22 awg all conductors |
| Strand Awg Size Per Conductor: |
| 36 all conductors |
| Conductor Arrangement And Quantity: |
| 1 twisted pair |
| Voltage Rating: |
| 1000.0 root mean square (rms) operating voltage all conductors |
| Special Features: |
| Primary insulation conforms to I-p-403 type 3 |
| Color: |
| White 2nd position cover second conductor |
| Material: |
| Silver 2nd position coating cable |
| Material Specification: |
| Astm b298 federal specification single material response core conductor all conductors |
| Precious Material And Location: |
| Surface all conductors silver and surface shield, braid silver |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Silver core conductor all conductors |
| Surface Treatment Specification: |
| Astm b298 assn standard single treatment response core conductor all conductors |
| Departure From Cited Designator: |
| As modified by strand quantity and strand awg size per conductor |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 6145-00-964-1230

Electrical Special Purpose Cable - Page 2 of 2



Demilitarization:

No

Fiig:

A077a0