## NSN 6145-01-011-7132

Electrical Power Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-011-7132

Cross Sectional Shape: Round Tempurature Rating: -65.0 degrees celsius and 200.0 degrees celsius Cross Section Outside Diameter: 0.176 inches Conductor Quantity: 2 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 18 awg all conductors Strand Awg Size Per Conductor: 30 all conductors Conductor Arrangement And Quantity: 2 singles
Tempurature Rating: -65.0 degrees celsius and 200.0 degrees celsius  Cross Section Outside Diameter: 0.176 inches  Conductor Quantity: 2  Strand Quantity Per Conductor: 19 all conductors  Conductor Form: Stranded all conductors  Round Conductor Size: 18 awg all conductors  Strand Awg Size Per Conductor: 30 all conductors  Conductor Arrangement And Quantity:
-65.0 degrees celsius and 200.0 degrees celsius  Cross Section Outside Diameter:  0.176 inches  Conductor Quantity: 2  Strand Quantity Per Conductor: 19 all conductors  Conductor Form: Stranded all conductors  Round Conductor Size: 18 awg all conductors  Strand Awg Size Per Conductor: 30 all conductors  Conductor Arrangement And Quantity:
Cross Section Outside Diameter:  0.176 inches  Conductor Quantity:  2  Strand Quantity Per Conductor:  19 all conductors  Conductor Form:  Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:
O.176 inches  Conductor Quantity: 2  Strand Quantity Per Conductor: 19 all conductors  Conductor Form: Stranded all conductors  Round Conductor Size: 18 awg all conductors  Strand Awg Size Per Conductor: 30 all conductors  Conductor Arrangement And Quantity:
Conductor Quantity:  2  Strand Quantity Per Conductor:  19 all conductors  Conductor Form:  Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:
Strand Quantity Per Conductor:  19 all conductors  Conductor Form:  Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:
Strand Quantity Per Conductor:  19 all conductors  Conductor Form:  Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:
19 all conductors  Conductor Form: Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:
Conductor Form: Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:
Stranded all conductors  Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:
Round Conductor Size:  18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:
18 awg all conductors  Strand Awg Size Per Conductor:  30 all conductors  Conductor Arrangement And Quantity:
Strand Awg Size Per Conductor: 30 all conductors  Conductor Arrangement And Quantity:
30 all conductors  Conductor Arrangement And Quantity:
Conductor Arrangement And Quantity:
2 singles
Voltage Rating:
600.0 root mean square (rms) operating voltage all conductors
Color:
White core conductor first conductor
Material:
Plastic polytetrafluoroethylene 1st position primary insulation all conductors
Material Specification:
Astm b298 assn standard single material response core conductor all conductors
Precious Material And Location:
Surface all conductors silver and surface shield, braid silver
Precious Material:
Silver
Surface Treatment:
Silver core conductor all conductors
Surface Treatment Specification:
Astm b298 assn standard single treatment response core conductor all conductors
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No.
Fiig:
A077a0