NSN 6145-01-133-2332

Cross Sectional Shape:

Twist

N/a

Electrical Special Purpose Cable - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6145-01-133-2332

-	Геmpurature Rating:					
-	-65.0 degrees celsius and 200.0 degrees celsius					
(Cross-sectional Height:					
(0.050 inches					
(Cross-sectional Width:					
(0.100 inches					
(Conductor Quantity:					
2	2					
;	Strand Quantity Per Conductor:					
•	19 all conductors					
(Conductor Form:					
,	Stranded all conductors					
ı	Round Conductor Size:					
2	22 awg all conductors					
;	Strand Awg Size Per Conductor:					
(34 all conductors					
(Conductor Arrangement And Quantity:					
2	2 twisted together w/no outer covering					
١	Voltage Rating:					
(600.0 root mean square (rms) operating voltage all conductors					
;	Special Features:					
I	Primary insulation conforms to I-p-403 type 3					
(Color:					
١	White 2nd position cover second conductor					
ı	Material:					
I	Plastic polytetrafluoroethylene 1st position primary insulation all conductors					
ı	Material Specification:					
/	Astm b298 federal specification single material response core conductor all conductors					
I	Precious Material And Location:					
,	Surface all conductors silver					
I	Precious Material:					
,	Silver					
;	Surface Treatment:					
,	Silver core conductor all conductors					
;	Surface Treatment Specification:					
,	Astm b298 assn standard single treatment response core conductor all conductors					
ı	Departure From Cited Document:					
,	As modified by strand quantity per conductor and awg strand size per conductor					
;	Shelf Life:					

NSN 6145-01-133-2332

Electrical Special Purpose Cable - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A077a0