## NSN 6145-01-137-7155

**Cross Sectional Shape:** 

A077a0

Electrical Special Purpose Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-137-7155

| Round   |
|---|
| Conductor Quantity:   |
| 59  |
| Color Coding Document:  |
| Cw-h0001-33875 drawing  |
| Strand Quantity Per Conductor:  |
| 19 all conductors   |
| Conductor Form:   |
| Stranded all conductors   |
| Round Conductor Size:   |
| 22 awg all conductors   |
| Strand Awg Size Per Conductor:  |
| 34 all conductors   |
| Conductor Arrangement And Quantity:   |
| 3 singles and 28 twisted pair   |
| Conductor Grouping Arrangement Type And Quantity:   |
| 3 singles all groups and 28 twisted pair all groups   |
| Conductor Sequence Within Groups:   |
| First conductor first group and second conductor first group and third conductor first group  |
| Voltage Rating:   |
| 600.0 root mean square (rms) operating voltage all conductors   |
| Special Features:   |
| Second grouping arrangement through twenty-ninth grouping arrangement fourth conductor through fifty-ninth conductor and multiconductor         |
| group covering material type and location tape plastic polyester (mylar) mil-i-631 type g form f subform tf class 1 twenty-first group through  |
| twenty-ninth group and shield braid copper tin covered twenty-first group throgh twenty-ninth group and jacket plastic nylon twenty-first group |
| through twenty-ninth group through twenty-ninth group or jacket plastic (tefzel) twenty-first group through twenty-ninth group and outer jacket |
| color green   |
| Material Specification:   |
| Astm b33 assn standard all material responses core conductor all conductors   |
| Surface Treatment:  |
| Tin core conductor all conductors   |
| Surface Treatment Specification:  |
| Astm b33-63 assn standard single treatment response core conductor all conductors   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |