

View Online at https://aerobasegroup.com/nsn/6145-01-169-8325

**Cross Sectional Shape:** 

Twist

**Tempurature Rating:** 

150.0 degrees celsius

### **Cross-sectional Height:**

0.040 inches

#### Cross-sectional Width:

0.080 inches

## **Conductor Quantity:**

2

#### Tracer Color:

Brown second tracer second conductor

#### Strand Quantity Per Conductor:

19 all conductors

### Conductor Form:

Stranded all conductors

#### **Round Conductor Size:**

24 awg all conductors

### Strand Awg Size Per Conductor:

36 all conductors

### **Conductor Arrangement And Quantity:**

1 twisted together w/no outer covering

#### Voltage Rating:

600.0 root mean square (rms) operating voltage all conductors

#### Color:

White 1st position cover all conductors

## Material:

Plastic polyalkene 1st position primary insulation all conductors

# Material Specification:

Astm b33 assn standard all material responses core conductor all conductors

## Surface Treatment:

Tin core conductor all conductors

# Surface Treatment Specification:

Astm b33-63 assn standard single treatment response core conductor all conductors

# Departure From Cited Document:

As modified by first and second tracer color per conductor

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Electrical Special Purpose Cable - Page 2 of 2



Fiig: A077a0

Mil-std (military Standard):

Mil-c-27500 spec.