NSN 6145-01-204-8928

Electrical Power Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-204-8928

Round Cross Section Outside Diameter: 1.220 inches Conductor Quantity: 24 Strand Quantity Per Conductor: 7 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 18 awg all conductors Stranded was Size Per Conductor: 26 all conductors Strand Awg Size Per Conductor: 26 all conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tr-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mili-Fa31, type g military specification single material response 3rd position tape all groups Surface Treatment Specification: Astm ba3-63 assn standard single treatment response core conductor all conductors Surface Treatment Specification: No Shelf Life: No Demilitarization: No Filig: A077a0	Cross Sectional Shape:
Cross Section Outside Diameter: 1.220 inches Conductor Quantity: 24 Strand Quantity Per Conductor: 7 all conductors Conductor Form: Strande all conductors Round Conductor Size: 18 awg all conductors Stranded all conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: 11 hird conductor second group and fourth conductor second group Special Features: Paint aluminum ttp-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material: Plastic polyester 2nd position tape all groups Material: Naterial Specification: Mili-631, type g military specification single material response 3rd position tape all groups Surface Treatment Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: Na Unit Of Measure:	
1.220 inches Conductor Quantity: 24 Strand Quantity Per Conductor: 7 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 18 awg all conductors Strand Awg Size Per Conductor: 26 all conductors Strand Awg Size Per Conductor: 26 all conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum ttp-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mill-ie31, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm 533-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit of Measure: Demilitarization: No Fig: A077-70 Mill-ie31 (military Standard):	
Conductor Quantity: 24 Strand Quantity Per Conductor: 7 all conductors Form: Stranded all conductors Round Conductor Stree: 18 awg all conductors Round Conductor Stree: 18 awg all conductors 25 all conductors 25 all conductors 26 all conductors 27 and Conductor Street 28 all conductors 29 all conductors 20 all conductors Sequence Within Groups: 11 trivial conductor Sequence Within Groups: 11 trivial conductor Sequence Within Groups: 12 twisted pair 20 conductor Sequence Within Groups: 21 twisted pair 22 conductor Sequence Within Groups: 23 all conductors Sequence Within Groups: 24 conductor Sequence Within Groups: 25 conductor Sequence Within Groups: 26 all conductor Sequence Within Groups: 27 all conductor Sequence Within Groups: 28 conductor Sequence Within Groups: 29 conductor Sequence Within Groups: 20 conductor Sequence Within Groups: 21 conductor Sequence Within Groups: 22 conductor Sequence Within Groups: 23 conductor Sequence Within Groups: 24 conductor Sequence Within Groups: 25 conductor Sequence Within Groups: 26 all conductor Sequence Within Groups: 26 all conductor Sequence Within Groups: 27 conductor Sequence Within Groups: 28 conductor Sequence Within Groups: 28 all conductor Sequence Within Groups: 29 conductor Sequence Within Groups: 20 co	
Strand Quantity Per Conductors 7 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 18 awg all conductors Stranded all conductors Stranded all conductors Stranded all conductors Stranded all conductors Strand Awg Size Per Conductor: 28 all conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum it-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mili-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: Na Unit of Measure: — Demilitarization: No Fig: A077a0 Mil-std (military Standard):	
Strand Quantity Per Conductors Conductor Form: Stranded all conductors Round Conductor Size: 18 awg all conductors Stranded all conductors Strand Awg Size Per Conductor: 26 all conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mill-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm 533-63 assn standard single treatment response core conductor all conductors Shelf Life: Via Unit of Measure: — Demilitarization: No Fig: A077a0 Mill-estd (military Standard):	•
7 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 18 awg all conductors Strand Awg Size Per Conductor: 26 all conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mill-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A077a0 Mill-std (military Standard):	
Conductor Form: Stranded all conductors Round Conductor Size: 18 awg all conductors Strand Awg Size Per Conductor: 26 all conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mill-1631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 asn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A077a0 Mill-1641 (military Standard):	
Stranded all conductors Round Conductor Size: 18 awg all conductors Strand Awg Size Per Conductor: 28 all conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-fruir dand twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductoral conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A077a0 Mil-i-std (military Standard):	
Round Conductor Size: 18 awg all conductors Strand Awg Size Per Conductor: 26 all conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mili-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 asan standard single treatment response core conductor all conductors Shelf Life: Na Unit Of Measure: Demilitarization: No Flig: A077a0 Mil-estd (military Standard):	
18 awg all conductors Strand Awg Size Per Conductor: 26 all conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A077a0 Mil-i-std (military Standard):	
Strand Awg Size Per Conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm ba3-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A07740 Mil-istd (military Standard):	
26 all conductors Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mill-i631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 asan standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A077a0 Mil-std (military Standard):	-
Conductor Arrangement And Quantity: 12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mil+631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A077a0 Mil-std (military Standard):	
12 twisted pair Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astn b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A077a0 Mil-istd (military Standard):	
Conductor Sequence Within Groups: Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A077a0 Mil-istd (military Standard):	
Third conductor second group and fourth conductor second group Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-istd (military Standard):	·
Special Features: Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A077a0 Mil-istd (military Standard):	
Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-i-std (military Standard):	
twenty-third and twenty-fourth conductor Material: Plastic polyester 2nd position tape all groups Material Specification: Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Paint aluminum tt-p-320 on armor and sixth grouping arrangement eleventh and twelfth conductor through twelfth grouping arrangement
Plastic polyester 2nd position tape all groups Material Specification: Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	
Material Specification: Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Material:
Mil-i-631, type g military specification single material response 3rd position tape all groups Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Plastic polyester 2nd position tape all groups
Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Material Specification:
Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Mil-i-631, type g military specification single material response 3rd position tape all groups
Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Surface Treatment:
Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Tin core conductor all conductors
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Surface Treatment Specification:
N/a Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Astm b33-63 assn standard single treatment response core conductor all conductors
Unit Of Measure: Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A077a0 Mil-std (military Standard):	N/a
No Fiig: A077a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A077a0 Mil-std (military Standard):	
Fiig: A077a0 Mil-std (military Standard):	Demilitarization:
A077a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A077a0
Mil-i-631 spec.	Mil-std (military Standard):
	Mil-i-631 spec.