NSN 6145-01-207-5168

Electrical Wire - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-207-5168

Round Conductor Size: 24 awg single conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 25.0. Toot mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure: — Demilitarization: No	
Tempurature Rating: 200.0 degrees celsius Cross Section Outside Diameter: 0.036 inches Tracer Color: Orange first tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Strandad single conductor Round Conductor Size: 24 awg single conductor Round Conductor Size: 24 awg single conductor Strand Awg Size Per Conductor: 32 single conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 32 single conductor Voltage Rating: 32 single single conductor White 1st position primary insulation single conductor Color: White 1st position primary insulation single conductor Material: Pleasic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Asim b298 asan standard single material response core conductor single conductor Precious Material: Silver Core conductor single conductor Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Asim b298 asan standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-18878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average', '', etc.). Shelf Life: Via Unit Of Measure:	
200.0 degrees celsius Cross Section Outside Diameter: 0.036 inches Tracer Color: Orange first tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 24 awg single conductor Strand Awg Size Per Conductor: 32 single conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Pleasic polysterafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average', '", etc.). Sheff Life: Na Unit Of Measure: Demilitarization: No	
Cross Section Outside Diameter: 0.036 inches Tracer Color: Orange first tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Strand Guantity Per Conductor Round Conductor Size: 24 awg single conductor Strand Awg Size Per Conductor: 32 single conductor Strand Awg Size Per Conductor: 32 single conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plassic polytetralluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver core conductor single conductor Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mill-w-168786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure:	
Tracer Color: Orange first tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Strand day single conductor Round Conductor Size: 24 awg single conductor Strand Awg Size Per Conductor: 32 single conductor Strand Awg Size Per Conductor: 32 single conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment Specification: Surface Treatment Specification: Surface Treatment Specification: Surface Treatment Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Shelf Life: Via Unit Of Measure: — Demilitarization: No	-
Tracer Color: Orange first tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 24 awg single conductor Strand Awg Size Per Conductor: 32 single conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 rot mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Silver Surface Treatment: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single material response core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-milw-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure: — Demilitarization: No	
Orange first tracer single conductor Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 24 awg single conductor Strand Awg Size Per Conductor: 32 single conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material: Silver Surface Treatment: Silver Core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: Silver Core conductor single conductor Surface Treatment Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', "average', "', etc.). Shelf Life: Na Unit Of Measure: — Demilitarization: No	
Strand Quantity Per Conductor: 7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 24 awg single conductor Strand Awg Size Per Conductor: 32 single conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material: Silver Dissertial: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Tost Data Document: Silver core conductor single conductor Surface Treatment Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: — Demilitarization: No	
7 single conductor Conductor Form: Stranded single conductor Round Conductor Size: 24 awg single conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Fost Data Document: 81349-mill-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheft Life: N/a Unit Of Measure: Demilitarization: No	
Conductor Form: Stranded single conductor Round Conductor Size: 24 awg single conductor Strand Awg Size Per Conductor: Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assan standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assan standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Strand Quantity Per Conductor:
Stranded single conductor Round Conductor Size: 24 awg single conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver ore conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	7 single conductor
Strand Awg Size Per Conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetraffuoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Conductor Form:
24 awg single conductor Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Fusions Material: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Stranded single conductor
Strand Awg Size Per Conductor: 32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Round Conductor Size:
32 single conductor Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Pleastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	24 awg single conductor
Voltage Rating: 250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Strand Awg Size Per Conductor:
250.0 root mean square (rms) operating voltage single conductor Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: — Demilitarization: No	32 single conductor
Color: White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astrn b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astrn b298 assn standard single treatment response core conductor single conductor Surface Treatment Specification: Astrn b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Voltage Rating:
White 1st position primary insulation single conductor Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	250.0 root mean square (rms) operating voltage single conductor
Material: Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Color:
Plastic polytetrafluoroethylene 1st position primary insulation single conductor Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	White 1st position primary insulation single conductor
Material Specification: Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Material:
Astm b298 assn standard single material response core conductor single conductor Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Plastic polytetrafluoroethylene 1st position primary insulation single conductor
Precious Material: Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Material Specification:
Silver Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Astm b298 assn standard single material response core conductor single conductor
Surface Treatment: Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Precious Material:
Silver core conductor single conductor Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Silver
Surface Treatment Specification: Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Surface Treatment:
Astm b298 assn standard single treatment response core conductor single conductor Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Silver core conductor single conductor
Test Data Document: 81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Surface Treatment Specification:
81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Astm b298 assn standard single treatment response core conductor single conductor
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	81349-mil-w-16878/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Shelf Life: N/a Unit Of Measure: Demilitarization: No	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No	
Demilitarization: No	N/a
Demilitarization: No	Unit Of Measure:
No	
No	Demilitarization:
	Fiig:
A077a0	