

View Online at <https://aerobasegroup.com/nsn/6145-01-216-6746>

**Cross Sectional Shape:**

Twist

**Tempurature Rating:**

-55.0 degrees celsius and 200.0 degrees celsius

**Cross-sectional Height:**

0.029 inches

**Cross-sectional Width:**

0.058 inches

**Conductor Quantity:**

2

**Strand Quantity Per Conductor:**

40 all conductors

**Conductor Form:**

Stranded all conductors

**Round Conductor Size:**

28 awg all conductors

**Strand Awg Size Per Conductor:**

44 all conductors

**Conductor Arrangement And Quantity:**

1 twisted together w/no outer covering

**Voltage Rating:**

300.0 root mean square (rms) operating voltage all conductors

**Special Features:**

Primary insulation polytetrafluoroethylene conforms to I-p-403 type 3 or primary insulation fluorinated ethylene propylene is per I-p-389

**Material:**

Plastic fluorinated ethylene propylene or plastic polytetrafluoroethylene 1st position primary insulation all conductors

**Material Specification:**

Qq-w-343, soft federal specification single material response core conductor all conductors

**Precious Material And Location:**

Surface all conductors silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver core conductor all conductors

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A077a0