

View Online at <https://aerobasegroup.com/nsn/6145-01-233-4796>

**Cross Sectional Shape:**

Twist

**Tempurature Rating:**

-65.0 degrees celsius and 200.0 degrees celsius

**Conductor Quantity:**

2

**Tracer Color:**

Brown first tracer all conductor

**Strand Quantity Per Conductor:**

19 all conductors

**Conductor Form:**

Stranded all conductors

**Round Conductor Size:**

20 awg all conductors

**Strand Awg Size Per Conductor:**

32 all conductors

**Voltage Rating:**

600.0 root mean square (rms) operating voltage all conductors

**Color:**

White 1st position cover all conductors

**Material:**

Plastic polytetrafluoroethylene 1st position primary insulation all conductors

**Material Specification:**

Astm b298 assn standard single material response core conductor all conductors

**Precious Material And Location:**

Surface all conductors and surface shield braid silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver core conductor all conductors

**Surface Treatment Specification:**

Astm b298 assn standard single treatment response core conductor all conductors

**Test Data Document:**

81349-mil-c-55021 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A077a0