NSN 6145-01-235-7639

Electrical Special Purpose Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-235-7639

Round Tempurature Rating: -55.0 degrees celsius and 125.0 degrees celsius Conductor Quantity: 6 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 31 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A077a0	Cross Sectional Shape:
Tempurature Rating: -55.0 degrees celsius and 125.0 degrees celsius Conductor Quantity: 6 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Pleastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Sheff Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
-55.0 degrees celsius and 125.0 degrees celsius Conductor Quantity: 6 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Conductor Quantity: 6 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-
Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
32 all conductors Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	20 awg all conductors
Conductor Arrangement And Quantity: 3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Strand Awg Size Per Conductor:
3 twisted pair Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	32 all conductors
Voltage Rating: 600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Conductor Arrangement And Quantity:
600.0 root mean square (rms) operating voltage all conductors Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3 twisted pair
Special Features: Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Voltage Rating:
Outer jacket is of braided construction Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	600.0 root mean square (rms) operating voltage all conductors
Color: Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
Black 1st position jacket cable Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Outer jacket is of braided construction
Material: Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Color:
Plastic polyvinylidene fluoride 1st position primary insulation all conductors Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Black 1st position jacket cable
Material Specification: Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Astm b33 assn standard all material responses core conductor all conductors Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Plastic polyvinylidene fluoride 1st position primary insulation all conductors
Surface Treatment: Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material Specification:
Tin core conductor all conductors Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Astm b33 assn standard all material responses core conductor all conductors
Surface Treatment Specification: Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Astm b33-63 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tin core conductor all conductors
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment Specification:
N/a Unit Of Measure: Demilitarization: No Fiig:	Astm b33-63 assn standard single treatment response core conductor all conductors
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
No Fiig:	Demilitarization:
Fiig:	
101140	