

View Online at <https://aerobasegroup.com/nsn/6145-01-237-2200>

**Cross Sectional Shape:**

Round

**Tempurature Rating:**

-65.0 degrees celsius and 200.0 degrees celsius

**Cross Section Outside Diameter:**

0.149 inches

**Conductor Quantity:**

2

**Strand Quantity Per Conductor:**

19 all conductors

**Conductor Form:**

Stranded all conductors

**Round Conductor Size:**

22 awg all conductors

**Strand Awg Size Per Conductor:**

34 all conductors

**Conductor Arrangement And Quantity:**

2 singles

**Voltage Rating:**

600.0 root mean square (rms) operating voltage all conductors

**Color:**

White 1st position primary insulation first conductorblack 1st position primary insulation second conductorwhite 3rd position jacket cable

**Material:**

Copper core conductor all conductorsplastic polytetrafluoroethylene 1st position primary insulation all conductorscopper 2nd position shield braid, metallic cableplastic polytetrafluoroethylene 3rd position jacket cable

**Material Specification:**

Astm b298 federal specification single material response core conductor all conductors

**Precious Material And Location:**

Surface all conductors silver and surface shield braid silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver core conductor all conductors

**Surface Treatment Specification:**

Astm b298 assn standard single treatment response 2nd position shield braid, metallic cable

**Departure From Cited Document:**

As modified by basic body color second conductor

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A077a0

**Mil-std (military Standard):**

Mil-c-27500 spec.