

View Online at <https://aerobasegroup.com/nsn/6145-01-243-9209>

**Cross Sectional Shape:**

Twist

**Tempurature Rating:**

-62.0 degrees celsius and 200.0 degrees celsius

**Conductor Quantity:**

2

**Tracer Color:**

Gray first tracer second conductor

**Color Coding Document:**

Mil-std-681-81349 standard

**Conductor Form:**

Solid all conductors

**Round Conductor Size:**

22 awg all conductors

**Conductor Arrangement And Quantity:**

1 twisted pair

**Voltage Rating:**

600.0 root mean square (rms) operating voltage all conductors

**Material:**

Plastic polytetrafluoroethylene 1st position primary insulation all conductors

**Material Specification:**

Mil-w-16878 military specification single material response 1st position primary insulation all conductors

**Test Data Document:**

81349-mil-c-55021 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-55021/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A077a0

**Mil-std (military Standard):**

Mil-w-16878 spec.