NSN 6145-01-253-3050

Electrical Special Purpose Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-253-3050

| view Online at https://aerobasegroup.com/nsn/o145-01-255-5656 |
|---|
| Cross Sectional Shape: |
| Round |
| Tempurature Rating: |
| -55.0 degrees celsius and 95.0 degrees celsius |
| Cross Section Outside Diameter: |
| 0.110 inches |
| Conductor Quantity: |
| 2 |
| Strand Quantity Per Conductor: |
| 150 all conductors |
| Conductor Form: |
| Stranded all conductors |
| Round Conductor Size: |
| 22 awg all conductors |
| Strand Awg Size Per Conductor: |
| 44 all conductors |
| Conductor Arrangement And Quantity: |
| 1 twisted pair |
| Voltage Rating: |
| 300.0 root mean square (rms) operating voltage all conductors |
| Special Features: |
| Aprimary insulation polytetrafluroethylene conforms to I-p-403, type 3 or primary insulation fluorinated ethylene propylene is per I-p-389; 1 |
| conductor insulator white; 1 conductor insulator blue |
| Color: |
| Clear 1st position jacket cable |
| Material: |
| Tin 2nd position shield braid, metallic cable |
| Material Specification: |
| Qq-w-343, soft federal specification single material response core conductor all conductors |
| Precious Material And Location: |
| Surface all conductors silver |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Silver core conductor all conductors |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A077a0