NSN 6145-01-255-9565

Radio Frequency Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-255-9565

| Cross Sectional Shape: |
|--|
| Round |
| Electrical Resistance: |
| |
| 50.0 ohms impedance |
| Cross Section Outside Diameter: |
| 0.086 inches |
| Conductor Quantity: |
| 1 |
| Capacitance In Picofarads: |
| 32.0 per foot |
| Conductor Form: |
| Solid single conductor |
| Round Conductor Size: |
| 24 awg single conductor |
| Conductor Arrangement And Quantity: |
| 1 coaxial |
| Voltage Rating: |
| 1500.0 root mean square (rms) operating voltage single conductor |
| Special Features: |
| Shield solid tin plated per mil-t-10727, type i |
| Material: |
| Plastic polytetrafluoroethylene 1st position primary insulation single conductor |
| Material Specification: |
| Astm b298 assn standard single material response core conductor single conductor |
| Precious Material And Location: |
| Surface single conductor silver |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Tin 2nd position tube single conductor |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A077a0 |
| |