NSN 6145-01-270-1575

Electrical Special Purpose Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-270-1575

Cross Sectional Shape: Round Tempurature Rating: -55.0 degrees celsius and 105.0 degrees celsius Cross Section Outside Diameter: 0.470 inches Conductor Quantity: 19 Color Coding Document: 424-0238-13499 drawing Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors Special Features:
Tempurature Rating: -55.0 degrees celsius and 105.0 degrees celsius Cross Section Outside Diameter: 0.470 inches Conductor Quantity: 19 Color Coding Document: 424-0238-13499 drawing Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Cross Section Outside Diameter: 0.470 inches Conductor Quantity: 19 Color Coding Document: 424-0238-13499 drawing Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Cross Section Outside Diameter: 0.470 inches Conductor Quantity: 19 Color Coding Document: 424-0238-13499 drawing Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Conductor Quantity: 19 Color Coding Document: 424-0238-13499 drawing Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Conductor Quantity: 19 Color Coding Document: 424-0238-13499 drawing Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Color Coding Document: 424-0238-13499 drawing Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Color Coding Document: 424-0238-13499 drawing Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Conductor Form: Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Stranded all conductors Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Round Conductor Size: 20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
20 awg all conductors Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Strand Awg Size Per Conductor: 32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
32 all conductors Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Conductor Arrangement And Quantity: 19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
19 singles Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
Voltage Rating: 1000.0 root mean square (rms) operating voltage all conductors
1000.0 root mean square (rms) operating voltage all conductors
Special Features:
-F
Outer jacket conforms to mil-i-631 class f
Color:
Black 1st position jacket cable
Material:
Plastic polyethylene terephthalate 1st position tape cable
Material Specification:
Astm b33 assn standard all material responses core conductor all conductors
Surface Treatment:
Tin core conductor all conductors
Surface Treatment Specification:
Astm b33-63 assn standard single treatment response core conductor all conductors
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A077a0