## NSN 6145-01-307-5508

Electrical Power Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-307-5508

Cross Sectional Shape:
Round
Cross Section Outside Diameter:
0.930 inches
Conductor Quantity:
6
Strand Quantity Per Conductor:
7 all conductors
Conductor Form:
Stranded all conductors
Round Conductor Size:
7 awg all conductors
Strand Awg Size Per Conductor:
15 all conductors
Conductor Arrangement And Quantity:
6 singles
Voltage Rating:
· chage ranng.
600.0 root mean square (rms) operating voltage all conductors
600.0 root mean square (rms) operating voltage all conductors
600.0 root mean square (rms) operating voltage all conductors  Material:
600.0 root mean square (rms) operating voltage all conductors  Material:  Plastic cross-linked polyolefin 3rd position jacket cable
600.0 root mean square (rms) operating voltage all conductors  Material:  Plastic cross-linked polyolefin 3rd position jacket cable  Surface Treatment:
600.0 root mean square (rms) operating voltage all conductors  Material:  Plastic cross-linked polyolefin 3rd position jacket cable  Surface Treatment:  Tin 2nd position shield braid, metallic cable
600.0 root mean square (rms) operating voltage all conductors  Material:  Plastic cross-linked polyolefin 3rd position jacket cable  Surface Treatment:  Tin 2nd position shield braid, metallic cable  Shelf Life:
600.0 root mean square (rms) operating voltage all conductors  Material:  Plastic cross-linked polyolefin 3rd position jacket cable  Surface Treatment:  Tin 2nd position shield braid, metallic cable  Shelf Life:  N/a
600.0 root mean square (rms) operating voltage all conductors  Material:  Plastic cross-linked polyolefin 3rd position jacket cable  Surface Treatment:  Tin 2nd position shield braid, metallic cable  Shelf Life:  N/a  Unit Of Measure:
600.0 root mean square (rms) operating voltage all conductors  Material:  Plastic cross-linked polyolefin 3rd position jacket cable  Surface Treatment:  Tin 2nd position shield braid, metallic cable  Shelf Life:  N/a  Unit Of Measure:
600.0 root mean square (rms) operating voltage all conductors  Material:  Plastic cross-linked polyolefin 3rd position jacket cable  Surface Treatment:  Tin 2nd position shield braid, metallic cable  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
600.0 root mean square (rms) operating voltage all conductors  Material:  Plastic cross-linked polyolefin 3rd position jacket cable  Surface Treatment:  Tin 2nd position shield braid, metallic cable  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No
600.0 root mean square (rms) operating voltage all conductors  Material:  Plastic cross-linked polyolefin 3rd position jacket cable  Surface Treatment:  Tin 2nd position shield braid, metallic cable  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:
600.0 root mean square (rms) operating voltage all conductors  Material:  Plastic cross-linked polyolefin 3rd position jacket cable  Surface Treatment:  Tin 2nd position shield braid, metallic cable  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig: