

View Online at <https://aerobasegroup.com/nsn/6145-01-340-4718>

Cross Sectional Shape:

Round

Tempurature Rating:

200.0 degrees celsius

Conductor Quantity:

5

Tracer Color:

Blue single tracer second conductororange single tracer third conductorgreen single tracer fourth conductorred single tracer fifth conductor

Strand Quantity Per Conductor:

19 all conductors

Conductor Form:

Stranded all conductors

Round Conductor Size:

20 awg all conductors

Strand Awg Size Per Conductor:

32 all conductors

Conductor Arrangement And Quantity:

5 singles

Voltage Rating:

600.0 root mean square (rms) operating voltage all conductors

Color:

White 1st position primary insulation all conductorswhite 3rd position jacket cable

Material:

Copper core conductor all conductorsplastic polytetrafluoroethylene 1st position primary insulation all conductorscopper 2nd position shield braid, metallic cableplastic polytetrafluoroethylene 3rd position jacket cable

Material Specification:

Astm b298 assn standard single material response core conductor all conductorsastm b298 assn standard single material response 2nd position shield braid, metallic cable

Precious Material And Location:

Surface all conductors silver and surface shield braid silver

Precious Material:

Silver

Surface Treatment:

Silver core conductor all conductorssilver 2nd position shield braid, metallic cable

Surface Treatment Specification:

Astm b298 assn standard single treatment response core conductor all conductorsastm b298 assn standard single treatment response 2nd position shield braid, metallic cable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A077a0

Mil-std (military Standard):

Mil-c-27500 spec.