NSN 6145-01-341-6928

Electrical Power Cable - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6145-01-341-6928

| Cross Sectional Shape: |
|------------------------------------------------------------------------------------------------------------------------------------|
| Twist |
| Tempurature Rating: |
| 200.0 degrees celsius |
| Cross-sectional Height: |
| 0.140 inches |
| Cross-sectional Width: |
| 0.070 inches |
| Conductor Quantity: |
| 2 |
| Zerrander Color: |
| Blue single tracer second conductor |
| Strand Quantity Per Conductor: |
| 19 all conductors |
| Conductor Form: |
| Stranded all conductors |
| Round Conductor Size: |
| 18 awg all conductors |
| Strand Awg Size Per Conductor: |
| 30 all conductors |
| Conductor Arrangement And Quantity: |
| 2 twisted together w/no outer covering |
| Voltage Rating: |
| 600.0 root mean square (rms) operating voltage all conductors |
| Color: |
| White 1st position primary insulation all conductors |
| Material: |
| Copper core conductor all conductorsplastic cross-linked modified ethylene tetrafluoroethylene 1st position primary insulation all |
| conductorsplastic cross-linked modified ethylene tetrafluoroethylene 2nd position jacket all conductors |
| Material Specification: |
| Astm b298 assn standard single material response core conductor all conductors |
| Precious Material And Location: |
| Surface all conductors silver |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Silver core conductor all conductors |
| Surface Treatment Specification: |
| Astm b298 assn standard single treatment response core conductor all conductors |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

-

NSN 6145-01-341-6928

Electrical Power Cable - Page 2 of 2



Demilitarization:

No

Fiig:

A077a0

Mil-std (military Standard):

Mil-c-27500 spec.