

View Online at <https://aerobasegroup.com/nsn/6145-01-342-5813>

**Cross Sectional Shape:**

Round

**Temperature Rating:**

200.0 degrees celsius

**Conductor Quantity:**

3

**Tracer Color:**

Blue single tracer second conductor orange single tracer third conductor

**Strand Quantity Per Conductor:**

19 all conductors

**Conductor Form:**

Stranded all conductors

**Round Conductor Size:**

24 awg all conductors

**Strand Awg Size Per Conductor:**

36 all conductors

**Conductor Arrangement And Quantity:**

3 singles

**Voltage Rating:**

600.0 root mean square (rms) operating voltage all conductors

**Color:**

White 1st position primary insulation all conductors white 3rd position jacket cable

**Material:**

Copper core conductor all conductors plastic polytetrafluoroethylene 1st position primary insulation all conductors copper 2nd position shield braid, metallic cable plastic fluorinated ethylene propylene 3rd position jacket cable

**Material Specification:**

Astm b298 assn standard single material response core conductor all conductors

**Precious Material And Location:**

Surface all conductors silver and surface shield braid silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver core conductor all conductors silver 2nd position shield braid, metallic cable

**Surface Treatment Specification:**

Astm b298 assn standard single treatment response core conductor all conductors astm b298 assn standard single treatment response 2nd position shield braid, metallic cable

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A077a0

**Mil-std (military Standard):**

Mil-c-27500 spec.