NSN 6145-01-345-1060

Electrical Special Purpose Cable - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6145-01-345-1060
Cross Sectional Shape:
Round
Tempurature Rating:
-65.0 degrees celsius and 200.0 degrees celsius
Cross Section Outside Diameter:
0.129 inches
Conductor Quantity:
3
Strand Quantity Per Conductor:
19 all conductors
Conductor Form:
Stranded all conductors
Round Conductor Size:
26 awg all conductors
Strand Awg Size Per Conductor:
38 all conductors
Conductor Arrangement And Quantity:
1 twisted pair
Voltage Rating:
600.0 root mean square (rms) operating voltage all conductors
Color:
Black 1st position primary insulation first conductorwhite 1st position primary insulation second conductorred 1st position primary insulation
third conductorwhite 3rd position jacket cable
Material:
Copper core conductor all conductorsplastic polytetrafluoroethylene 1st position primary insulation all conductorscopper 2nd position shield
braid, metallic cableplastic polytetrafluoroethylene 3rd position jacket cable
Material Specification:
Astm b298 assn standard single material response core conductor all conductors
Precious Material And Location:
Surface all conductors silver and surface shield braid silver
Precious Material:
Silver
Surface Treatment:
Silver core conductor all conductorssilver 2nd position shield braid, metallic cable
Surface Treatment Specification:
Astm b298 assn standard single treatment response core conductor all conductorsastm b298 assn standard single treatment response 2nd
position shield braid, metallic cable
Departure From Cited Document:
As modified by strand quantity per conductor and strand awg size per conductor
Shelf Life:
N/a
Unit Of Measure:

. .

Demilitarization:

NSN 6145-01-345-1060

Electrical Special Purpose Cable - Page 2 of 2



Fiig:

A077a0