

View Online at <https://aerobasegroup.com/nsn/6145-01-346-3915>

**Cross Sectional Shape:**

Round

**Tempurature Rating:**

150.0 degrees celsius

**Conductor Quantity:**

1

**Strand Quantity Per Conductor:**

19 single conductor

**Conductor Form:**

Stranded single conductor

**Round Conductor Size:**

16 awg single conductor

**Strand Awg Size Per Conductor:**

29 single conductor

**Conductor Arrangement And Quantity:**

1 singles

**Voltage Rating:**

600.0 root mean square (rms) operating voltage single conductor

**Color:**

White 2nd position jacket single conductorwhite 4th position jacket single conductor

**Material:**

Copper core conductor single conductorplastic cross-linked polyalkene 1st position primary insulation single conductorplastic cross-linked polyvinylidene fluoride 2nd position jacket single conductorcopper 3rd position shield braid, metallic single conductorplastic cross-linked modified ethylene tetrafluoroethylene 4th position jacket single conductor

**Material Specification:**

Astm b33 assn standard single material response core conductor single conductor

**Surface Treatment:**

Tin core conductor single conductortin 3rd position shield braid, metallic single conductor

**Surface Treatment Specification:**

Astm b33 assn standard single treatment response core conductor single conductorastm b33 assn standard single treatment response 3rd position shield braid, metallic single conductor

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A077a0

**Mil-std (military Standard):**

Mil-c-27500 spec.