## NSN 6145-01-347-2167

Electrical Special Purpose Cable - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6145-01-347-2167 **Cross Sectional Shape:** Round **Tempurature Rating:** 200.0 degrees celsius **Conductor Quantity: Tracer Color:** Blue single tracer second conductor **Strand Quantity Per Conductor:** 19 all conductors **Conductor Form:** Stranded all conductors **Round Conductor Size:** 22 awg all conductors **Strand Awg Size Per Conductor:** 34 all conductors **Conductor Arrangement And Quantity:** 2 singles **Voltage Rating:** 600.0 root mean square (rms) operating voltage all conductors Color: White 1st position primary insulation all conductorswhite 4th position jacket cablewhite 6th position jacket cable Material: Copper alloy core conductor all conductorsplastic cross-linked modified ethylene tetrafluoroethylene 1st position primary insulation all conductorsplastic cross-linked modified ethylene tetrafluoroethylene 2nd position jacket all conductorscopper 3rd position shield braid, metallic cableplastic cross-linked modified ethylene tetrafluoroethylene 4th position jacket cablecopper 5th position shield braid, metallic cableplastic cross-linked modified ethylene tetrafluoroethylene 6th position jacket cable **Material Specification:** Astm b298 assn standard single material response core conductor all conductors **Precious Material And Location:** Surface all conductors silver and surface shields braid silver **Precious Material:** Silver **Surface Treatment:** Silver core conductor all conductorssilver 3rd position shield braid, metallic cablesilver 5th position shield braid, metallic cable **Surface Treatment Specification:** Astm b298 assn standard single treatment response core conductor all conductors Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

**Demilitarization:** 

## NSN 6145-01-347-2167

Electrical Special Purpose Cable - Page 2 of 2



Mil-std (military Standard):

Mil-c-27500 spec.