

View Online at <https://aerobasegroup.com/nsn/6145-01-351-8704>

Cross Sectional Shape:

Round

Electrical Resistance:

50.00 ohms impedance

Cross Section Outside Diameter:

0.071 inches

Conductor Quantity:

1

Capacitance In Picofarads:

32.0 per foot

Strand Quantity Per Conductor:

7 single conductor

Conductor Form:

Stranded single conductor

Round Conductor Size:

28 awg single conductor

Strand Awg Size Per Conductor:

36 single conductor

Conductor Arrangement And Quantity:

1 coaxial

Voltage Rating:

750.0 root mean square (rms) operating voltage single conductor

Material:

Steel core conductor single conductor and copper core conductor single conductor plastic polytetrafluoroethylene 1st position primary insulation single conductor copper 2nd position shield braid, metallic single conductor plastic perfluoroalkoxy 3rd position jacket single conductor

Material Specification:

Astm b501 assn standard single material response core conductor single conductor

Precious Material And Location:

Surface single conductor silver and surface shield braid silver

Precious Material:

Silver

Surface Treatment:

Silver core conductor single conductor silver 2nd position shield braid, metallic single conductor

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A077a0