

View Online at <https://aerobasegroup.com/nsn/6145-01-356-5134>

Cross Sectional Shape:

Round

Cross Section Outside Diameter:

0.113 inches

Conductor Quantity:

4

Tracer Color:

Red single tracer first conductor green single tracer second conductor black single tracer fourth conductor

Strand Quantity Per Conductor:

19 all conductors

Conductor Form:

Stranded all conductors

Round Conductor Size:

24 awg all conductors

Strand Awg Size Per Conductor:

36 all conductors

Conductor Arrangement And Quantity:

2 twisted pair

Group Quantity:

2

Conductor Grouping Arrangement Type And Quantity:

2 twisted pair all groups

Conductor Sequence Within Groups:

First conductor first group and second conductor first group third conductor second group and fourth conductor second group

Voltage Rating:

600.0 root mean square (rms) operating voltage all conductors

Color:

White 1st position primary insulation all conductors black 4th position jacket cable

Material:

Copper alloy core conductor all conductors plastic polytetrafluoroethylene 1st position primary insulation all conductors copper 2nd position shield braid, metallic all groups plastic fluorinated ethylene propylene 3rd position jacket all groups plastic polyurethane 4th position jacket cable

Material Specification:

Mil-w-22759/23 military specification single material response core conductor all conductors

Precious Material And Location:

Surface shields braid silver

Precious Material:

Silver

Surface Treatment:

Nickel core conductor all conductor silver 2nd position shield braid, metallic all groups

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A077a0

Mil-std (military Standard):

Mil-w-22759 spec.