

View Online at <https://aerobasegroup.com/nsn/6145-01-360-9284>

Cross Sectional Shape:

Round

Tempurature Rating:

150.0 degrees celsius

Cross Section Outside Diameter:

0.078 inches

Conductor Quantity:

1

Strand Quantity Per Conductor:

19 single conductor

Conductor Form:

Stranded single conductor

Round Conductor Size:

24 awg single conductor

Strand Awg Size Per Conductor:

36 single conductor

Conductor Arrangement And Quantity:

1 singles

Voltage Rating:

600.0 root mean square (rms) operating voltage single conductor

Special Features:

Optional identification method a applies per par. 3.2.1.1.2 of mil-c-27500g

Color:

White 3rd position jacket single conductor

Material:

Plastic cross-linked modified ethylene tetrafluoroethylene 3rd position jacket single conductor

Material Specification:

Astm b33 assn standard single material response 2nd position shield braid, metallic single conductor

Precious Material And Location:

Surface single conductor. Silver

Precious Material:

Silver

Surface Treatment:

Tin 2nd position shield braid, metallic single conductor

Surface Treatment Specification:

Astm b33 assn standard single treatment response 2nd position shield braid, metallic single conductor

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A077a0

Mil-std (military Standard):

Mil-c-27500 spec.