

View Online at <https://aerobasegroup.com/nsn/6145-01-360-9284>

**Cross Sectional Shape:**

Round

**Tempurature Rating:**

150.0 degrees celsius

**Cross Section Outside Diameter:**

0.078 inches

**Conductor Quantity:**

1

**Strand Quantity Per Conductor:**

19 single conductor

**Conductor Form:**

Stranded single conductor

**Round Conductor Size:**

24 awg single conductor

**Strand Awg Size Per Conductor:**

36 single conductor

**Conductor Arrangement And Quantity:**

1 singles

**Voltage Rating:**

600.0 root mean square (rms) operating voltage single conductor

**Special Features:**

Optional identification method a applies per par. 3.2.1.1.2 of mil-c-27500g

**Color:**

White 3rd position jacket single conductor

**Material:**

Plastic cross-linked modified ethylene tetrafluoroethylene 3rd position jacket single conductor

**Material Specification:**

Astm b33 assn standard single material response 2nd position shield braid, metallic single conductor

**Precious Material And Location:**

Surface single conductor. Silver

**Precious Material:**

Silver

**Surface Treatment:**

Tin 2nd position shield braid, metallic single conductor

**Surface Treatment Specification:**

Astm b33 assn standard single treatment response 2nd position shield braid, metallic single conductor

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A077a0

**Mil-std (military Standard):**

Mil-c-27500 spec.