

View Online at <https://aerobasegroup.com/nsn/6145-01-372-3039>

Cross Sectional Shape:

Round

Electrical Resistance:

75.00 ohms impedance

Cross Section Outside Diameter:

0.140 inches

Conductor Quantity:

1

Capacitance In Picofarads:

19.0 per foot

Strand Quantity Per Conductor:

19 single conductor

Conductor Form:

Stranded single conductor

Round Conductor Size:

28 awg single conductor

Strand Awg Size Per Conductor:

40 single conductor

Conductor Arrangement And Quantity:

1 coaxial

Voltage Rating:

900.0 root mean square (rms) operating voltage single conductor

Color:

White 1st position primary insulation single conductor brown 5th position jacket single conductor

Material:

Copper alloy core conductor single conductor plastic fluorinated ethylene propylene 1st position primary insulation single conductor copper 2nd position shield braid, metallic single conductor plastic fluorinated ethylene propylene 3rd position secondary insulation single conductor steel 4th position shield braid, metallic single conductor and copper 4th position shield braid, metallic single conductor plastic fluorinated ethylene propylene 5th position jacket single conductor

Precious Material And Location:

Surface single conductor silver and surface shields braid silver

Precious Material:

Silver

Surface Treatment:

Silver core conductor single conductor silver 2nd position shield braid, metallic single conductor silver 4th position shield braid, metallic single conductor

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A077a0