

View Online at <https://aerobasegroup.com/nsn/6145-01-375-1369>

**Cross Sectional Shape:**

Round

**Tempurature Rating:**

150.0 degrees celsius

**Conductor Quantity:**

1

**Strand Quantity Per Conductor:**

19 single conductor

**Conductor Form:**

Stranded single conductor

**Round Conductor Size:**

22 awg single conductor

**Strand Awg Size Per Conductor:**

34 single conductor

**Conductor Arrangement And Quantity:**

1 singles

**Voltage Rating:**

600.0 root mean square (rms) operating voltage single conductor

**Color:**

White 1st position primary insulation single conductorwhite 5th position jacket single conductor

**Material:**

Copper core conductor single conductorplastic cross-linked modified ethylene tetrafluoroethylene 1st position primary insulation single conductorplastic cross-linked modified ethylene tetrafluoroethylene 2nd position jacket single conductorcopper 3rd position shield braid, metallic single conductorcopper 4th position shield braid, metallic single conductorplastic cross-linked modified ethylene tetrafluoroethylene 5th position jacket single conductor

**Material Specification:**

Astm b33 assn standard single material response core conductor single conductor

**Surface Treatment:**

Tin core conductor single conductortin 3rd position shield braid, metallic single conductortin 4th position shield braid, metallic single conductor

**Surface Treatment Specification:**

Astm b33 assn standard single treatment response core conductor single conductorastm b33 assn standard single treatment response 3rd position shield braid, metallic single conductorastm b33 assn standard single treatment response 4th position shield braid, metallic single conductor

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A077a0

**Mil-std (military Standard):**

Mil-c-27500 spec.