## NSN 6145-01-377-3714

Electrical Power Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-377-3714

Tempurature Rating: 150.0 degrees celsius Cross Section Outside Diameter: 0.193 inches Conductor Quantity: 2 Tracer Color: Blue single tracer second conductor Strand Quantity Per Conductor: 19 all conductors Conductor Form:
150.0 degrees celsius  Cross Section Outside Diameter: 0.193 inches  Conductor Quantity: 2  Tracer Color: Blue single tracer second conductor  Strand Quantity Per Conductor: 19 all conductors
Cross Section Outside Diameter:  0.193 inches  Conductor Quantity:  2  Tracer Color:  Blue single tracer second conductor  Strand Quantity Per Conductor:  19 all conductors
0.193 inches  Conductor Quantity: 2  Tracer Color: Blue single tracer second conductor  Strand Quantity Per Conductor: 19 all conductors
Conductor Quantity: 2 Tracer Color: Blue single tracer second conductor Strand Quantity Per Conductor: 19 all conductors
Tracer Color: Blue single tracer second conductor Strand Quantity Per Conductor: 19 all conductors
Tracer Color: Blue single tracer second conductor Strand Quantity Per Conductor: 19 all conductors
Blue single tracer second conductor  Strand Quantity Per Conductor:  19 all conductors
Strand Quantity Per Conductor:  19 all conductors
19 all conductors
Conductor Form:
Stranded all conductors
Round Conductor Size:
16 awg all conductors
Strand Awg Size Per Conductor:
29 all conductors
Conductor Arrangement And Quantity:
2 singles
Voltage Rating:
600.0 root mean square (rms) operating voltage all conductors
Color:
White 4th position jacket cable
Material:
Plastic cross-linked modified ethylene tetrafluoroethylene 4th position jacket cable
Material Specification:
Astm b33 assn standard single material response core conductor all conductors
Surface Treatment:
Tin core conductor all conductors
Surface Treatment Specification:
Astm b33 assn standard single treatment response core conductor all conductors
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A077a0