NSN 6145-01-379-9713

Electrical Power Cable - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6145-01-379-9713

| Cross Sectional Shape: |
|--|
| Twist |
| Tempurature Rating: |
| 200.0 degrees celsius |
| Cross-sectional Height: |
| 0.396 inches |
| Cross-sectional Width: |
| 0.396 inches |
| Conductor Quantity: |
| 4 |
| Tracer Color: |
| Orange single tracer third conductor |
| Strand Quantity Per Conductor: |
| 37 all conductors |
| Conductor Form: |
| Stranded all conductors |
| Round Conductor Size: |
| 12 awg all conductors |
| Strand Awg Size Per Conductor: |
| 28 all conductors |
| Conductor Arrangement And Quantity: |
| 4 twisted together w/no outer covering |
| Voltage Rating: |
| 600.0 root mean square (rms) operating voltage all conductors |
| Color: |
| White 3rd position coating all conductors |
| Material: |
| Plastic fluorinated ethylene propylene 2nd position tape all conductors and plastic polyimide 2nd position tape all conductors and plastic |
| fluorinated ethylene propylene 2nd position tape all conductors |
| Material Specification: |
| Astm b298 assn standard single material response core conductor all conductors |
| Precious Material And Location: |
| Surface all conductors silver |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Silver core conductor all conductors |
| Surface Treatment Specification: |
| Astm b298 assn standard single treatment response core conductor all conductors |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

__

NSN 6145-01-379-9713

Electrical Power Cable - Page 2 of 2



Demilitarization:

No

Fiig:

A077a0

Mil-std (military Standard):

Mil-c-27500 spec.