NSN 6145-01-408-2802

Electrical Special Purpose Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-408-2802

| Cross Sectional Shape: |
|---|
| Round |
| Tempurature Rating: |
| -65.0 degrees celsius and 200.0 degrees celsius |
| Cross Section Outside Diameter: |
| 0.138 inches |
| Conductor Quantity: |
| 2 |
| Strand Quantity Per Conductor: |
| 19 all conductors |
| Conductor Form: |
| Stranded all conductors |
| Round Conductor Size: |
| 24 awg all conductors |
| Strand Awg Size Per Conductor: |
| 36 all conductors |
| Voltage Rating: |
| 600.0 root mean square (rms) operating voltage all conductors |
| Color: |
| White 1st position primary insulation all conductors |
| Material: |
| Plastic polytetrafluoroethylene 3rd position jacket cable |
| Material Specification: |
| Astm b298 assn standard single material response core conductor all conductors |
| Precious Material And Location: |
| Surface all conductors silver and surface shield braid silver |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Silver core conductor all conductors |
| Surface Treatment Specification: |
| Astm b298 assn standard single treatment response core conductor all conductors |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A077a0 |