## NSN 6145-01-424-6549

Radio Frequency Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-424-6549

Cross Sectional Shape:
Round
Electrical Resistance:
53.0 ohms impedance
Cross Section Outside Diameter:
0.195 inches
Conductor Quantity:
1
Capacitance In Picofarads:
28.8 per foot
Conductor Form:
Solid single conductor
Round Conductor Size:
20 awg single conductor
Conductor Arrangement And Quantity:
1 coaxial
Color:
Black 3rd position jacket single conductor
Black 3rd position jacket single conductor  Material:
Material:
Material: Plastic polyethylene 1st position primary insulation single conductor
Material: Plastic polyethylene 1st position primary insulation single conductor Surface Treatment:
Material: Plastic polyethylene 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor
Material: Plastic polyethylene 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Shelf Life:
Material: Plastic polyethylene 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Shelf Life: N/a
Material: Plastic polyethylene 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Shelf Life: N/a
Material:  Plastic polyethylene 1st position primary insulation single conductor  Surface Treatment:  Tin 2nd position shield braid, metallic single conductor  Shelf Life:  N/a  Unit Of Measure:
Material: Plastic polyethylene 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Shelf Life: N/a Unit Of Measure: Demilitarization:
Material:  Plastic polyethylene 1st position primary insulation single conductor  Surface Treatment:  Tin 2nd position shield braid, metallic single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No
Material: Plastic polyethylene 1st position primary insulation single conductor Surface Treatment: Tin 2nd position shield braid, metallic single conductor Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: