NSN 6145-01-425-7807

Electrical Special Purpose Cable - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6145-01-425-7807

Cross Sectional Shape:
Round
Tempurature Rating:
260.0 degrees celsius
Conductor Quantity:
2
Tracer Color:
Blue single tracer second conductor
Strand Quantity Per Conductor:
19 all conductors
Conductor Form:
Stranded all conductors
Round Conductor Size:
22 awg all conductors
Strand Awg Size Per Conductor:
34 all conductors
Conductor Arrangement And Quantity:
2 singles
Voltage Rating:
600.0 root mean square (rms) operating voltage all conductors
Color:
White 6th position braid, non-metallic cable
Bartanial.
Material:
Rubber silicone class q 1st position primary insulation all conductors
Rubber silicone class q 1st position primary insulation all conductors
Rubber silicone class q 1st position primary insulation all conductors Material Specification:
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors Surface Treatment:
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors Surface Treatment: Nickel core conductor all conductors
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors Surface Treatment: Nickel core conductor all conductors Surface Treatment Specification:
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors Surface Treatment: Nickel core conductor all conductors Surface Treatment Specification: Astm b355 assn standard single treatment response core conductor all conductors
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors Surface Treatment: Nickel core conductor all conductors Surface Treatment Specification: Astm b355 assn standard single treatment response core conductor all conductors Shelf Life:
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors Surface Treatment: Nickel core conductor all conductors Surface Treatment Specification: Astm b355 assn standard single treatment response core conductor all conductors Shelf Life: N/a
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors Surface Treatment: Nickel core conductor all conductors Surface Treatment Specification: Astm b355 assn standard single treatment response core conductor all conductors Shelf Life: N/a
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors Surface Treatment: Nickel core conductor all conductors Surface Treatment Specification: Astm b355 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure:
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors Surface Treatment: Nickel core conductor all conductors Surface Treatment Specification: Astm b355 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization:
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors Surface Treatment: Nickel core conductor all conductors Surface Treatment Specification: Astm b355 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No
Rubber silicone class q 1st position primary insulation all conductors Material Specification: Astm b355 assn standard single material response core conductor all conductors Surface Treatment: Nickel core conductor all conductors Surface Treatment Specification: Astm b355 assn standard single treatment response core conductor all conductors Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: