

View Online at <https://aerobasegroup.com/nsn/6145-01-580-6407>

End Application:

Craftalt c/a-523d slep a/c sys- dual 33k btu uni

Special Features:

Rsc aerospace and defense td-005583 19 conductor water-blocked lightweight shipboard cablecomponent i: m81044 16awg conductor: 16awg tin coated copper insulation: irradiation cross-linked polyalkene jacket: irradiation cross-linked pvdf. Component ii: m81044 8awg conductor: 8awg tin coated copper insulation: irradiation cross-linked polyalkene jacket: irradiation cross-linked pvdf. Component iii: m81044 12awg conductor: 12awg tin coated copper insulation: irradiation cross-linked polyalkene jacket: irradiation cross-linked pvdf. Component iv: conductor: 4awg tin coated copper insulation: irradiation cross-linked polyalkene. Cable cable fill: all cable interstices filled with silicone binder: applied helically with overlap. Jacket: irradiation cross-linked low smoke zero halogen jacket (black). Diameter .900 inch cable identification: the jacket shall be printed as follows lcac/19-41821211165w rsc aerospace adn defense 61123 year

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A077a0