NSN 6150-00-192-1915

Electrical Power Cable Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6150-00-192-1915

Round Overall Length: 25.083 feet Cross Section Outside Diameter: 1.324 inches Conductor Quantity: 34 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 16 awg all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demillitarization: Yes - demil/mli Fiig:	Cross Sectional Shape:
25.083 feet Cross Section Outside Diameter: 1.324 inches Conductor Quantity: 34 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 16 awg all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	·
25.083 feet Cross Section Outside Diameter: 1.324 inches Conductor Quantity: 34 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 16 awg all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Overall Length:
1.324 inches Conductor Quantity: 34 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 16 awg all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	_
Conductor Quantity: 34 Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 16 awg all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Cross Section Outside Diameter:
Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 16 awg all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	1.324 inches
Strand Quantity Per Conductor: 19 all conductors Conductor Form: Stranded all conductors Round Conductor Size: 16 awg all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Conductor Quantity:
Conductor Form: Stranded all conductors Round Conductor Size: 16 awg all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	34
Conductor Form: Stranded all conductors Round Conductor Size: 16 awg all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Strand Quantity Per Conductor:
Stranded all conductors Round Conductor Size: 16 awg all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	19 all conductors
Round Conductor Size: 16 awg all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Conductor Form:
Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Stranded all conductors
Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Round Conductor Size:
Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	16 awg all conductors
Conductor Arrangement And Quantity: 17 twisted pair Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Strand Awg Size Per Conductor:
Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	29 all conductors
Voltage Rating: 3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Conductor Arrangement And Quantity:
3000.0 dielectric test voltage all conductors Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	17 twisted pair
Special Features: 1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Voltage Rating:
1 dust cap Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	3000.0 dielectric test voltage all conductors
Material: Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Special Features:
Plastic polyethylene 2nd position jacket all conductors Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	1 dust cap
Style Designator: Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Material:
Jack and internal angle connector Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Plastic polyethylene 2nd position jacket all conductors
Fsc Application Data: Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Style Designator:
Cable assembly set, launch control Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Jack and internal angle connector
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Fsc Application Data:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Cable assembly set, launch control
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
_	Yes - demil/mli
A077a0	Fiig:
AUTTAU	A077a0