

View Online at https://aerobasegroup.com/nsn/6150-00-993-5633

Cross Sectional Shape: Round Overall Length: 256.000 inches Termination Type: Connector receptacle both ends all conductors Conductor Quantity: 4 Strand Quantity Per Conductor: 19 4th conductor Conductor Form: Stranded all conductors Strand Awg Size Per Conductor: 29 all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig: A077a0	
Overall Length:256.000 inchesFermination Type:Connector receptacle both ends all conductorsConductor Quantity:4Strand Quantity Per Conductor:19 4th conductorConductor Form:Stranded all conductorsStrand Awg Size Per Conductor:29 all conductorsConductor Arrangement And Quantity:4 singlesVoltage Rating:600.0 ac rated working voltage all conductorsTerminal Commercial And Government Entity Code:81205 2nd end all conductorsMaterial:Plastic 1st position primary insulation all conductorsStyle Designator:Jack and external connectorFsc Application Data:Launch control system, guided missileShelf Life:IvaYaPinititrizzation:Yes - demil/mliFig:	
256.000 inches Fermination Type: Connector receptacle both ends all conductors Conductor Quantity: 4 Strand Quantity Per Conductor: 19 4th conductor Conductor Form: Strand Aug Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit Of Measure: - Demilitarization: Yes - demil/mli	
Fermination Type: Connector receptacle both ends all conductors Conductor Quantity: 4 Strand Quantity Per Conductor: 19 4th conductor Conductor Form: Strand all conductors Strand Aug Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fec Application Data: Launch control system, guided missile Shelf Life: Na Unit of Measure: - Demilitarization: re Demilitarization: Yes - demil/mli	
Connector receptacle both ends all conductors Coductor Quantity: 4 Strand Quantity Per Conductor: 19 4th conductor Conductor Form: Strand de all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit of Measure: Demilitarization: Yes - demil/mli Fig:	
Conductor Quantity: 4 Strand Quantity Per Conductor: 19 4th conductor Conductor Form: Stranded all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Utof Measure: Demilitarization: Yes - demil/mli	
4 Strand Quantity Per Conductor: 19 4th conductor Conductor Form: Stranded all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fac Application Data: Launch control system, guided missile Sheft Life: Na Tori Of Measure: r- Femilitarization: Fig:	
Strand Quantity Per Conductor: 19 4th conductor Conductor Form: Stranded all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit Of Measure: - Fig:	Conductor Quantity:
19 4th conductor Conductor Form: Stranded all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit Of Measure: Fase Institution: Yes - demil/mli	
Conductor Form:Stranded all conductorsStrand Awg Size Per Conductor:29 all conductorsConductor Arrangement And Quantity:4 singlesVoltage Rating:600.0 ac rated working voltage all conductorsTerminal Commercial And Government Entity Code:81205 2nd end all conductorsMaterial:Plastic 1st position primary insulation all conductorsStyle Designator:Jack and external connectorFsc Application Data:Launch control system, guided missileShelf Life:N/aUnit Of Measure:Fmilitarization:Yes - demil/mliFig:	
Strande all conductors Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Sc Application Data: Launch control system, guided missile Sheff Life: N/a Unit Of Measure: Fminitarization: Yes - demil/mli Fig:	19 4th conductor
Strand Awg Size Per Conductor: 29 all conductors Conductor Arrangement And Quantity: 4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	
29 all conductors Conductor Arrangement And Quantity: 4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Stranded all conductors
Conductor Arrangement And Quantity:4 singlesVoltage Rating:600.0 ac rated working voltage all conductorsTerminal Commercial And Government Entity Code:81205 2nd end all conductorsMaterial:Plastic 1st position primary insulation all conductorsStyle Designator:Jack and external connectorFsc Application Data:Launch control system, guided missileShelf Life:N/aDemilitarization:Fig:	Strand Awg Size Per Conductor:
4 singles Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Mit Of Measure: Temilitarization: Yes - demil/mli	29 all conductors
Voltage Rating: 600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit Of Measure: - Sterial: Pomilitarization: Yes - demil/mli	Conductor Arrangement And Quantity:
600.0 ac rated working voltage all conductors Terminal Commercial And Government Entity Code: 81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	4 singles
Terminal Commercial And Government Entity Code:81205 2nd end all conductorsMaterial:Plastic 1st position primary insulation all conductorsStyle Designator:Jack and external connectorFsc Application Data:Launch control system, guided missileShelf Life:N/aUnit Of Measure:Permilitarization:Yes - demil/mliFig:	Voltage Rating:
81205 2nd end all conductors Material: Plastic 1st position primary insulation all conductors Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Mit Of Measure: Pemilitarization: Yes - demil/mli Fiig:	600.0 ac rated working voltage all conductors
Material:Plastic 1st position primary insulation all conductorsStyle Designator:Jack and external connectorFsc Application Data:Launch control system, guided missileShelf Life:N/aUnit Of Measure:Pemilitarization:Yes - demil/mliFig:	Terminal Commercial And Government Entity Code:
Plastic 1st position primary insulation all conductorsStyle Designator:Jack and external connectorFsc Application Data:Launch control system, guided missileShelf Life:N/aUnit Of Measure:Pemilitarization:Yes - demil/mliFig:	81205 2nd end all conductors
Style Designator: Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Material:
Jack and external connector Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Plastic 1st position primary insulation all conductors
Fsc Application Data: Launch control system, guided missile Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Style Designator:
Launch control system, guided missile Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Jack and external connector
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Fsc Application Data:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Launch control system, guided missile
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
 Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
	Yes - demil/mli
A077a0	Fiig:
	A077a0