NSN 6150-01-029-8649

Electrical Lead - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6150-01-029-8649

Round Leadlength: Between 5.000 inches and 5.500 inches Conductor Form: Stranded single conductor Round Conductor Size: 23 awg single conductor Lead Pull Strength: 10.0 pounds Special Features: Special Features: Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control C7770a, line no. 0090 Color: Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure: Demilitarization:	
Between 5.000 inches and 5.500 inches Conductor Form: Stranded single conductor Round Conductor Size: 23 awg single conductor Lead Pull Strength: 10.0 pounds Special Features: Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control C7770a, line no. 0090 Color: Black core conductor single conductor Material: Plastic viryl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Conductor Form: Stranded single conductor Round Conductor Size: 23 awg single conductor Lead Pull Strength: 10.0 pounds Special Features: Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control C7770a, line no. 0090 Color: Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Stranded single conductor Round Conductor Size: 23 awg single conductor Lead Pull Strength: 10.0 pounds Special Features: Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control C7770a, line no. 0090 Color: Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Round Conductor Size: 23 awg single conductor Lead Pull Strength: 10.0 pounds Special Features: Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control C7770a, line no. 0090 Color: Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
23 awg single conductor Lead Pull Strength: 10.0 pounds Special Features: Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control C7770a, line no. 0090 Color: Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Lead Pull Strength: 10.0 pounds Special Features: Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control C7770a, line no. 0090 Color: Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Special Features: Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control C7770a, line no. 0090 Color: Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Special Features: Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control C7770a, line no. 0090 Color: Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control C7770a, line no. 0090 Color: Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
C7770a, line no. 0090 Color: Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Color: Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	n plant equipment contained in individual repair parts ordering data instrumentation control no.
Black core conductor single conductor Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Material: Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Plastic vinyl 1st position primary insulation single conductor Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Surface Treatment: Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Tin core conductor single conductor Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	single conductor
Reference Number Differentiating Characteristics: As differentiated by special features Shelf Life: N/a Unit Of Measure:	
As differentiated by special features Shelf Life: N/a Unit Of Measure:	
Shelf Life: N/a Unit Of Measure:	acteristics:
N/a Unit Of Measure: 	
Unit Of Measure:	
 Demilitarization:	
Demilitarization:	
20111110112011011	
No	
Fiig:	
A077a0	