NSN 6150-01-088-3805

Conductor Bus - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6150-01-088-3805

Flat Overall Length: 1.000 inches Cross-sectional Height: 0.017 inches Cross-sectional Width: 0.080 inches End Application: F-16 acft Mounting Configuration: Ten 0.045 to 0.048 in. Diameter holes equally spaced, beginning 0.050 in. From c of ea end hole Construction: Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment: Tin
1.000 inches Cross-sectional Height: 0.017 inches Cross-sectional Width: 0.080 inches End Application: F-16 acft Mounting Configuration: Ten 0.045 to 0.048 in. Diameter holes equally spaced, beginning 0.050 in. From c of ea end hole Construction: Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Cross-sectional Height: 0.017 inches Cross-sectional Width: 0.080 inches End Application: F-16 acft Mounting Configuration: Ten 0.045 to 0.048 in. Diameter holes equally spaced, beginning 0.050 in. From c of ea end hole Construction: Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Cross-sectional Width: 0.080 inches End Application: F-16 acft Mounting Configuration: Ten 0.045 to 0.048 in. Diameter holes equally spaced, beginning 0.050 in. From c of ea end hole Construction: Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Cross-sectional Width: 0.080 inches End Application: F-16 acft Mounting Configuration: Ten 0.045 to 0.048 in. Diameter holes equally spaced, beginning 0.050 in. From c of ea end hole Construction: Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
0.080 inches End Application: F-16 acft Mounting Configuration: Ten 0.045 to 0.048 in. Diameter holes equally spaced, beginning 0.050 in. From c of ea end hole Construction: Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
End Application: F-16 acft Mounting Configuration: Ten 0.045 to 0.048 in. Diameter holes equally spaced, beginning 0.050 in. From c of ea end hole Construction: Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
F-16 acft Mounting Configuration: Ten 0.045 to 0.048 in. Diameter holes equally spaced, beginning 0.050 in. From c of ea end hole Construction: Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Mounting Configuration: Ten 0.045 to 0.048 in. Diameter holes equally spaced, beginning 0.050 in. From c of ea end hole Construction: Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Ten 0.045 to 0.048 in. Diameter holes equally spaced, beginning 0.050 in. From c of ea end hole Construction: Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Construction: Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Solid Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Material: Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Copper Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Material Specification: Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Qq-c-502, 1/2h federal specification single material response Surface Treatment:
Surface Treatment:
Tin
1111
Surface Treatment Specification:
Mil-t-10727, type 1 military specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A537p0
Mil-std (military Standard):
Mil-t-10727 spec.