

View Online at <https://aerobasegroup.com/nsn/6150-01-347-6876>

**End Application:**

Lantirn

**Termination Type:**

Connector all ends all conductors

**Usage Design:**

Power

**Binding Method:**

Sleeve and wire bound

**Conductor Quantity:**

285

**Cable Assemblylength:**

60.000 inches

**Branch Quantity:**

7

**Special Features:**

C/o 1 conn, plug; 1 conn, access; 1 conn, elec, circ, coverr; 1 conn, recep; 2 housing, elec conn; 2 conn, access; 1 conn, elec; 2 adapter, elec conn; 2 cover, conn access; 1 conn, rect; 1 cover, conn; 1 conn, elec, rect; 1 backshell, conn; 1 conn cover; 1 conn, rrecep; 1 housing, elec conn; 1 conn, elec; 12 shield term, solder style; 8 solder sleeve; 6 screw, mach pan head; 3 ring, ret; 3 spring, hel; 3 jackscrew; 1 transition, heat shrink; 2 strap, tiedown; 1 boot, overexpanded; a/r adhesive, hot melt, tape; insul sleeving, ht shrink; solder, tin alloy; sleeving, expandable; wire, elec; cable, elec shld, unshld; braid, wire, shld; sealing, locking, retaining; cable, rf; soldering; cappingw/crimp or heat shrink

**Material:**

Copper core conductor all conductors

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A077a0