NSN 6150-01-352-6461

Electrical Special Purpose Cable Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6150-01-352-6461

view Offilite at https://aerobasegroup.com/nsn/0100-01-302-0401
Cross Sectional Shape:
Round
Overall Length:
11.400 feet
Termination Type:
Connector plug both ends all conductors
Conductor Quantity:
49
Conductor Form:
Stranded all conductors
Conductor Arrangement And Quantity:
23 singles and 7 twisted pair and 4 twisted triples
Group Quantity:
3
Conductor Grouping Arrangement Type And Quantity:
23 singles first group7 twisted pair second group4 twisted triples third group
Terminal Manufacturer Identifying Reference Number:
Ms27467t25b61sb 1st end all conductorsms3475w24-61px 2nd end all conductors
Terminal Commercial And Government Entity Code:
96906 both ends all conductors
Special Features:
Owire/cable conforming to m81044/12-22-9, m27500-22ml3t08, m27500-22ml2t08, m27500-20ml2t08; all shields are terminated to both
connectors; color code: pairs white & white/blue, triples white & white/blue & white/orange
Color:
White 1st position primary insulation first groupwhite 4th position jacket second groupwhite 4th position jacket third groupblack 6th position
sleeve cable
Material:
Copper core conductor all conductorsplastic cross-linked polyalkene 1st position primary insulation all conductorsplastic cross-linked
polyvinylidene fluoride 2nd position secondary insulation all conductorscopper 3rd position shield braid, metallic second groupcopper 3rd
position shield braid, metallic third groupplastic cross-linked polyvinylidene fluoride 4th position jacket second groupplastic cross-linked
polyvinylidene fluoride 4th position jacket third groupcopper 5th position shield braid, metallic cableplastic polyester 6th position sleeve cable
Material Specification:
Qqb575r30t0562 federal specification 8th material response 3rd position shield braid, metallic cable
Surface Treatment:
Tin core conductor all conductorstin 3rd position shield braid, metallic second grouptin 3rd position shield braid, metallic third grouptin 5th
position shield braid, metallic cable
Style Designator:
Internal angle and internal straight connector
Shelf Life:
N/a
Unit Of Measure:

Fiia:

Demilitarization: Yes - demil/mli