

View Online at <https://aerobasegroup.com/nsn/6150-01-356-8643>

End Application:

Apu installation, c-17

Termination Type:

Connector 1st end all conductorsconnector 2nd end all conductorsconnector 3rd end all conductorsconnector 4th end all conductorsconnector 5th end all conductorsconnector 6th end all conductorsconnector 7th end all conductorsconnector 8th end all conductorsconnector 9th end all conductorsconnector 10th end all conductors

Usage Design:

Power

Binding Method:

Braid and sleeve and wire bound

Conductor Quantity:

126

Cable Assemblylength:

130.000 inches

Terminal Manufacturer Identifying Reference Number:

Ms24266r12t3s7 1st end all conductorsms3459kt28-21pn 2nd end all conductorsms3459kt28-21pw 3rd end all conductorsms3459l10sl-3s 4th end all conductors223-584-9026 5th end all conductors223-584-9027 6th end all conductors223-584-9028 7th end all conductors223-584-9029 8th end all conductors223-584-9030 9th end all conductors223-588-9008 10th end all conductors

Branch Quantity:

25

Special Features:

1 term 724-524-9904; 2 terminal ms25036-102; 5 term, chromel 724-505-9013; 5 term, alumel 724-505-9014; wire mil-w-22759/11f silver coated; cable, thermocouple 192-505-9001

Material:

Copper core conductor all conductorsplastic polytetrafluoroethylene 1st position primary insulation all conductors

Surface Treatment:

Nickel core conductor all conductors

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A077a0