

View Online at <https://aerobasegroup.com/nsn/6150-01-362-6015>

Cross Sectional Shape:

Round

Overall Length:

30.000 feet

Tempurature Rating:

260.0 degrees celsius

End Application:

An/alr-46/6 (v) ; nha 89012-10000

Termination Type:

Connector plug 1st end all conductorsunprocessed 2nd end all conductors

Usage Design:

Power

Conductor Quantity:

5

Strand Quantity Per Conductor:

19 all conductors

Conductor Form:

Stranded all conductors

Round Conductor Size:

20 awg all conductors

Strand Awg Size Per Conductor:

32 all conductors

Conductor Arrangement And Quantity:

5 singles

Voltage Rating:

600.0 root mean square (rms) operating voltage all conductors

Terminal Manufacturer Identifying Reference Number:

Ms27467t11f98s 1st end all conductors

Terminal Commercial And Government Entity Code:

96906 1st end all conductors

Special Features:

Noun: cable assembly, power, electrical (w5); green wire spliced using wire m16878/4bfe5 & splice m83519/1-5, and terminated at backshell of p1, & p1-e; cable conforms to m27500a20rc5s06

Color:

Red 1st position primary insulation first conductorblue 1st position primary insulation second conductororange 1st position primary insulation third conductorwhite 1st position primary insulation fourth conductorgreen 1st position primary insulation fifth conductorwhite 3rd position jacket cable

Material:

Copper core conductor all conductorsplastic polytetrafluoroethylene 1st position primary insulation all conductorscopper 2nd position shield braid, metallic cableplastic polytetrafluoroethylene 3rd position jacket cable

Precious Material And Location:

Shield & conductor plating silver

Precious Material:

Silver

Surface Treatment:

Style Designator:

Internal connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A077a0