Electrical Power Cable Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6150-01-368-8494

Cit	oss Sectional Shape:
Rou	und
Ove	erall Length:
120	0.000 inches
Ter	npurature Rating:
200	).0 degrees celsius
Cro	oss Section Outside Diameter:
0.0	80 inches
End	d Application:
Sco	ppe shield ph ii
Ter	mination Type:
Cor	nnector 1st end all conductorsconnector plug 2nd end all conductors
Usa	age Design:
Pov	ver
Со	nductor Quantity:
4	
Stra	and Quantity Per Conductor:
19 ;	all conductors
Со	nductor Form:
Stra	anded all conductors
Ro	und Conductor Size:
16 :	awg all conductors
Stra	and Awg Size Per Conductor:
29 :	all conductors
Со	nductor Arrangement And Quantity:
4 si	ingles
Vol	tage Rating:
600	0.0 root mean square (rms) operating voltage all conductors
Ter	minal Manufacturer Identifying Reference Number:
Ms	3108e32-8s 1st end all conductors5965vy 2nd end all conductors
Ter	minal Commercial And Government Entity Code:
969	006 1st end all conductors83315 2nd end all conductors
Spe	ecial Features:
Wir	e, 16awg, wht, tfe p/n m16878/4bje9; cable, 4 cond, shld, color brn, red, yel, orn, p/n ss-160329; dwg title cable assembly, power supply
120	Ovac input
Col	lor:
Wh	ite 1st position cover all conductors
Mat	terial:
Cop	oper core conductor all conductorsplastic polytetrafluoroethylene 1st position primary insulation all conductors
Sty	le Designator:
Inte	ernal angle and external straight connector
	elf Life:

N/a

Electrical Power Cable Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A077a0