

View Online at <https://aerobasegroup.com/nsn/6150-01-439-1303>

**Cross Sectional Shape:**

Round

**Tempurature Rating:**

150.0 degrees celsius

**End Application:**

Nha p/n 3156194; u/o an/gsm-396

**Termination Type:**

Connector both ends all conductors

**Conductor Quantity:**

4

**Tracer Color:**

Orange first tracer third conductor

**Strand Quantity Per Conductor:**

19 all conductors

**Conductor Form:**

Stranded all conductors

**Product Name:**

Cable assembly, interface, umbilical

**Round Conductor Size:**

20 awg all conductors

**Strand Awg Size Per Conductor:**

32 all conductors

**Conductor Arrangement And Quantity:**

4 singles

**Terminal Manufacturer Identifying Reference Number:**

Ms3471w16-23p 2nd end all conductors

**Special Features:**

600v maximum oper volt; cable, elec p/ns m27500-20ml4t08, m27500-w0ml2t08; wire, elec p/ns m81044/12-20-9, m81044/12-16-9; braid, wire p/n qqb575r36t0500

**Color:**

White 1st position jacket cable

**Material:**

Tin 2nd position shield braid, metallic cable

**Material Specification:**

Astm b33 assn standard all material responses core conductor all conductors

**Surface Treatment:**

Tin core conductor all conductors

**Surface Treatment Specification:**

Astm b33-63 assn standard single treatment response core conductor all conductors

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A077a0